

Quilt Designed By: Cyndi Hershey
Finished Quilt Size: 49" x 65"

Designed by: Cyndi Hershey





24790 G



24791 G



24793 G



24793 K



24777 E



24778 F



24778 T



24792 K

QUILT REQUIREMENTS		
		12 Kits
Design:	Yards	Bolts
24790 G	(1) 24" panel	1
24791 G	2	2
24793 G (inc. binding)	1¼	1
24793 K	½	1
24777 E	¾	1
24778 F	½	1
24778 T	⅓	1
24792 K (backing)	4	4

Cutting

Note: All strips are cut across the width of the fabric (perpendicular to the selvages) unless noted otherwise. Also, ¼" seam allowance is assumed.

A. 24790 G (panel)

- Cut panel ¼" beyond printed edge of design. This should measure approximately 23" x 40½"

B. 24791 G (deer scenic)

- Cut (2) 5½" strips from the *length of the fabric (parallel to selvages)*.

Note: To match the quilt image, cut these from the side where the screen dots are printed within the selvage. (side borders)

- From remaining width, cut (6) 5½" strips. Matching pattern, sew strips together into two sets. Trim each set to 5½" x 54". (top/bottom borders)

C. 24793 G (green tree landscape)

- Cut (2) 3½" strips from the *length of the fabric (parallel to selvages)*.
- From remaining width of fabric, cut (2) 3" strips and (8) 2½" strips for binding.

D. 24793 K (gray tree landscape)

- Cut (3) 2⅞" strips; subcut (32) 2⅞" squares. Cut each square diagonally in half to create sixty-four half-square triangles.
- Cut (1) 4½" strip; subcut (4) 4½" squares. From remainder of strip, cut (2) 2½" x 4½" rectangles. Then, cut (2) 2½" x 4½" rectangles in the opposite direction.

E. 24777 E (tonal sand leaves)

- Cut (6) 1½" strips.
- Cut (3) 2⅞" strips; subcut (32) 2⅞" squares. Cut each square diagonally in half to create sixty-four half-square triangles. From remainder of strip, cut (4) 2½" squares.

F. 24778 F (tonal evergreen scroll)

- Cut (6) 1½" strips.
- Cut (1) 2½" strip; subcut (4) 2½" squares.

G. 24778 T (tonal terracotta scroll)

- Cut (5) 1½" strips. Sew three strips together end to end with diagonal seams; press. From this, cut (2) 1½" x 60" strips.

Construction


Block A (4" finished)

1. Sew one (E) 1½" strip to one (F) 1½" strip along the long side. Press toward the green strip. Repeat to make six strip sets. Cut strip sets into (144) 1½" segments.
2. Sew two strip segments together into a four-patch unit. Press. Repeat to make seventy-two units.



Make 72

- Sew one (D) $2\frac{7}{8}$ " triangle to one (E) $2\frac{7}{8}$ " triangle. Press. Repeat to make sixty-four half-square-triangle units.



Make 64

- Sew two units from step 2 with two units from step 3 to make one Block A. Press seams in alternate direction in top and bottom row then join rows; press. Repeat to make thirty-two Block A.
Note: There will be eight four-patch units remaining to be used in Block B.



Make 32

Block B (4" finished)

- Sew two strip set segments from step 2 together (remaining from Block A); press. Repeat to make four units.



Make 4

- Sew one (D) $2\frac{1}{2}$ " x $4\frac{1}{2}$ " rectangle to bottom of unit from step 1. Press. Repeat to make four Block B.



Make 4

Block C (4" finished)

Note: In order to keep the direction of the gray tonal print upright in all blocks, the triangles are placed in different corners on each of the four blocks. Refer to diagrams for correct placement.

- Draw a line on the back side of each (E) and (F) $2\frac{1}{2}$ " square. With right sides together, place a marked (E) square on one corner of a (D) $4\frac{1}{2}$ " square. Sew on the line. Trim seam to $\frac{1}{4}$ ". Press seam toward the resulting triangle. Repeat by sewing a marked (F) square on the opposite corner. Make four Block C as shown.



Assembly

- Center and sew one (C) $3\frac{1}{2}$ " strip to both sides of the panel. Trim ends of strips even with panel. Press toward the strips. Center and sew one (C) 3" strip to the top and bottom of the panel. Trim ends of strips even with framed panel. Press toward the strips.
- Keeping panel centered, trim framed panel to $28\frac{1}{2}$ " x $44\frac{1}{2}$ ".
- Sew ten Block A's with one Block B as shown to make one side border. Pay attention to the direction of print in Block B so you use the correct block. Press. Repeat.



Left Border



Right Border

4. Sew six Block A's, one Block B and two Block C's together to create top and bottom borders. Pay attention to the direction of print in Blocks B and C so you use the correct blocks.



Top Border



Bottom Border

5. Sew side borders to quilt. Press seams toward the inner frame. Sew top and bottom borders to the quilt. Press seams toward the inner frame.



6. Center and sew one (G) 1½" x 60" strip to one (B) 5½" side border. (Pay attention to the direction of print in the (B) strip.) Press toward the (B) strip. Center border set to side of quilt. Begin and end sewing a generous ¼" from edge of quilt. Repeat process for other side of quilt.
7. Center and sew one (G) 1½" x WOF strip to one (B) 5½" top/bottom border. (Pay attention to the direction of print in the (B) strip.) Press toward the (B) strip. Center border set to top of quilt. Begin and end sewing a generous ¼" from edge of quilt. Repeat process for bottom of quilt.
8. Close corners with mitered seams. Trim seam allowance to ½" and press seams open. Press borders away from center of quilt.

Finishing

1. Prepare backing with vertical seam/s. Press seams open.
2. Layer backing, batting and quilt top. Baste and quilt as desired.
3. Trim layers even with quilt top.
4. Prepare binding with (C) 2½" strips. Sew binding to quilt using your preferred method.